

Technical Data Sheet

PropTracSM Proppants

Description



Hexion's PropTracSM Fracture Diagnostics System is an environmentally acceptable method to determine propped fracture height. PropTrac incorporates a non-radioactive tag into the resin coating of proppants. This Smart Proppant[™] technology is activated by a logging tool after the proppants have been placed in the fracture. The data received is analyzed to identify the location of the tagged proppant and provide accurate information.

Application

The PropTrac fracture diagnostics service is a simpler, easier, and safer way to optimize fracture treatments and improve treatment results.

Benefits

The PropTrac service offers the following benefits:

- Does not use radioactive tracer materials as in conventional tracer jobs
- No special environmental or safety precautions, permits, or regulatory compliance are necessary
- Logs can be run as often as desired during the life of the well
- Proppants with a built-in tagging material in the resin coating provide more accurate results

Technical Advantage

The actual resin coated proppant is delivered already tagged as compared to conventional tracer jobs where small additional radioactive tracer materials are continuously added to the proppant slurry. Since the proppant has the tag built-in to the coating, there is no guesswork as to where the proppant is actually located in the fracture.

The PropTrac product does not use radioactive tracer materials as in conventional tracer jobs. Utilizing a patented coating technology, it offers an environmentally acceptable alternative to the personnel performing the fracture treatment and flowback. Unlike conventional radioactive tracer logging services, no special environmental or safety precautions, permits or regulatory compliance are necessary.

PropTrac logs can be run as often as desired during the life of the well. There are no concerns about radioactive half-life decay. It can also allow you to observe how proppant distribution in the fracture may be affected by changes in flowing pressure, flow rates or fluid entry. The information provided in the report can also be used to assist in analyzing refrac options during the life of the well.

Contact Information

Hexion
Oilfield Technology Group
15366 Park Row
Houston, Texas 77084 USA
+1 281 646 2800
www.hexion.com/oilfield

Customer Service
+1 800 626 2116
otg.customerservice@hexion.com

Technical Inquiries
otg.customerservice@momentive.com

PropTracSM Proppants

<https://hexioninternet-hexioninternet-slave.azurewebsites.net/en-US/product/proptrac>

Generated: April 19, 2024

Issue Date:

Revision:

® and ™ Licensed trademarks of Hexion Inc.

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. **HEXION MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION**, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.