

Technical Data Sheet

EPIKURE™ Curing Agent 8545-W-52

Product Description

EPIKURE Curing Agent 8545-W-52 is a non-ionic, water reducible, modified epoxy-amine adduct supplied at 52% solids in water. This product is a versatile, unique, new curing agent that can be combined with the whole range of standard or diluted liquid epoxy resins as well as with epoxy resin emulsions and/or dispersions. Due to its versatility, the product is the ideal candidate to use in a wide range of applications.

Application Areas/Suggested Uses

Different from other products in the market, EPIKURE 8545-W-52 can be used in civil engineering applications as well as in high performance anti-corrosive primer formulations. In either application, this curing agent offers the general benefit of requiring no or an extremely low co-solvent level whilst giving optimum performance.

In civil engineering applications, EPIKURE 8545-W-52 can be used in sealers, self levelling flooring and concrete coatings where it can be combined with liquid, diluted or water dispersible epoxy resins and where it offers an excellent colour stability and a visible end of pot-life. The product is very easy to handle and has excellent rheological properties, when applied with either roller, brush or spray gun.

In combination with epoxy resin dispersions, EPIKURE 8545-W-52 can be used for 100% waterborne heavy duty anti-corrosive coatings, even in marine environment: it offers fast drying, cure down to 10°C, excellent corrosion and chemical resistance.

Benefits

- Zero VOC
- Benzyl alcohol free
- Very low free amine level
- Visible end of pot-life
- Solution and colour stability

Safety, Storage & Handling

Please refer to the MSDS for the most current Safety and Handling information.

EPIKURE 8545-W-52 should be stored in tightly sealed, lined containers in a dry location at normal room temperatures. Under these conditions the shelf life should be a minimum of three years from date of certification.

Exposure to these materials should be minimized and avoided, if feasible, through the observance of proper precautions, use of appropriate engineering controls and proper personal protective clothing and equipment, and adherence to proper handling procedures. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheet (MSDS) for these and all other products being used are understood by all persons who will work with them.

Questions and requests for information on Hexion, Inc. ("Hexion") products should be directed to your Hexion sales representative, or the nearest Hexion sales office. Information and MSDSs on non-Hexion products should be obtained from the respective manufacturer.

For literature and technical assistance, visit our website at www.hexion.com

EPIKURE Curing Agent 8545-W-52

<https://hexioninternet-hexioninternet-slave.azurewebsites.net/en-US/product/epikure-curing-agent-8545-w-52>

Generated: July 4, 2022

Issue Date:

Revision: 6/1/2010 12:00:00 AM

© and ™ Licensed trademarks of Hexion Inc.

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. **HEXION MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION**, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.