

# Technical Data Sheet

## HELOXY™ Modifier HD

### Product Description

HELOXY™ Modifier HD is adiglycidyl ether of 1,6-hexanediol.

The modifier is primarily used as a reactive diluent or viscosity reducer for liquid epoxy resins.

### Application Areas/Suggested Uses

HELOXY™ Modifier HD is a reactive diluent for a variety of uses for solvent-free coatings based on epoxy resins. Its main fields of application are formulated, low-viscous epoxy resins with good leveling, surfaces and wetting properties, used for civil engineering, paints and adhesives.

HELOXY™ Modifier HD is added to the epoxy resin in a ratio of 5 – 25 %.

### Benefits

- Reduces viscosity while maintaining most cured state properties
- Improves wetting characteristics
- Facilitates air release

### Sales Specifications

Property	Value	Unit	Test Method	Standard
Color	50 max	Hazen		ISO 6271
Epoxy Equivalent	135 - 155	g/equivalent	DIN 16945	
Epoxy Number	27.75 - 31.85	%	DIN 16945	
Viscosity at 25°C	14 - 25	mPa:s	DIN 16945	

### Typical Properties

Property	Value	Unit	Test Method	Standard
Delivery Form	liquid			
Density at 20°C	1.05 - 1.07	kg/L		ISO 2811
Hydrolyzable Chlorine Content	0.3	%		ISO 21627-2
Refractive Index at 25°C	1.458 - 1.462		DIN 51423	

### Safety, Storage & Handling

Please refer to the MSDS for the most current Safety and Handling information.

HELOXY™ Modifier HD should be stored at room temperature in conditions such that moisture is excluded, in the original containers kept tightly closed. Under these conditions the shelf life should be a minimum of three years from the date of certification.

HELOXY Modifier HD  
<https://hexioninternet-hexioninternet-slave.azurewebsites.net/en-US/product/heloxymodifier-hd>

Generated: August 14, 2022  
 Issue Date:  
 Revision: 4/1/2009 12:00:00 AM

© and ™ Licensed trademarks of Hexion Inc.

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. **HEXION MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION**, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.