


Technical Data Sheet

AcTivator™ Consolidation Aid

Description



Hexion's AcTivator™ consolidation aid is a low temperature consolidation aid for curable resin coated proppants (RCPs). This advanced product will help provide low-temperature consolidation of our SB Prime™, Prime Plus™, SB Excel™, SiberProp™, and OilPlus™ proppants.

Our AcTivator Oil™ consolidation aid is available for use in oil-based treatment fluids. Please consult your Hexion representative for more information on optimized concentration recommendations based on individual well conditions.

Typical Applications

- For reservoirs which typically produce proppant after fracturing
- For reservoirs with bottom-hole static temperatures in the range from 70 - 160°F [21 - 71°C]

Technical Advantages and Benefits

- Allows for consolidation to occur with Hexion's curable RCPs in low temperature applications
- Compatible with most aqueous fracturing fluid additives (e.g., gelling agents, breakers, cross-linkers, surfactants, foamers, etc.)
- Can be an excellent candidate for use with Hexion's resin coated proppants

Typical Properties

AcTivator™ Consolidation Aid

<https://hexioninternet-hexioninternet-slave.azurewebsites.net/en-US/product/activator>

Generated: July 1, 2022

Issue Date:

Revision:

© and ™ Licensed trademarks of Hexion Inc.

The information provided herein was believed by Hexion Inc. ("Hexion") to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by Hexion are subject to Hexion's terms and conditions of sale. **HEXION MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY HEXION**, except that the product shall conform to Hexion's specifications. Nothing contained herein constitutes an offer for the sale of any product.

Property	Value	Unit
Viscosity, Neat @ 77°F [25°C]	<1	cP
Chemical Type	Surfactant in alcohol	
Color	Colorless to pale yellow	
Density at 68°F [20°C]	0.92	g/cm ³
Density 68°F [20°C]	7.65	lbm/gal
Flash Point	54 [12]	°F [°C]
Freezing Point	< -12 [-24]	°F [°C]
Ionic Character	Nonionic	
Physical State	Liquid	
Shelf-Life	24	months
Solubility in Water, & Light Brine	Miscible (all proportions)	weight %
Solubility In Heavy Brine & Acid	Soluble to dispersible	weight %
Solubility In Oil	Insoluble to dispersible	weight %
Specific gravity at 68°F [20°C]	0.92	

For Best Results

- Should be mixed into all the fluid in which curable RCP is carried
- Should be added before the cross-linker
- Loading should be based on the liquid portion of the slurry only
- Lab testing should be performed to determine the requirements for fluid compatibility

Technical Considerations

- The use of excessive AcTivator consolidation aids may cause oversoftening and sloughening of the resin coating
- May be incompatible with gelled oil frac fluids, use AcTivator Oil consolidation aid in these cases
- As with all chemicals, test for fluid compatibility prior to using and consult your Hexion representative for proper usage

Contact Information

Hexion
Oilfield Technology Group
15366 Park Row
Houston, Texas 77084 USA
+1 281 646 2800
www.hexion.com/oilfield

Customer Service
+1 800 626 2116
otg.customerservice@hexion.com

Technical Inquiries
otg.customerservice@momentive.com